

WALLBOX DUO

Two sockets
in compact
housing

The Enelion Wallbox Duo is a two-socket car charging point. The device is capable of dynamically sharing the power between the two connected cars to optimize the charging process.



Solid
construction



Wide range
of communication



Building power
balancing

ANODIZED ALUMINUM

Advanced design

The design of the device allows for any configuration of connecting the power cables from the top or bottom of the charger. The output power for Wallbox Duo is 7.4 kW per socket, and for Wallbox Duo Power and Adspace it is 22 kW per socket. Optionally, the device can be equipped with a **Bridge communication module**, which allows you to connect to the Internet via **WiFi / Ethernet** or optionally **LTE (GSM)**. As standard, the devices have touch buttons for menu navigation.

Elegance

Aesthetics is our leitmotif. The housing is made of anodized aluminum and is available in two colors: silver and graphite-black. The front of the device is made of hardened plastic to protect it from scratches. The device has two charging sockets, an RFID card reader and an OLED display. In addition, the charger status is communicated via LED diodes located next to the sockets.

COMMUNICATION

Internet connection

One **Enelion Bridge** module is enough to control up to 90 stations in the charger network. Use **WiFi, Ethernet** or optional **LTE(GSM)**, depending on your needs.

Dynamic Load Balancing (DLB)

Networking multiple charging stations together opens the way to data exchange between them. As a result, they can control the current energy consumption and share the power in an optimal way.

OCPP Protocol

Enelion chargers are compatible with the OCPP 1.6. Thanks to this, you can use the **Enelion Administrative System** or other compatible.

Wallbox with two sockets

Duo series Wallboxes provide convenience use – two charging points in one housing. Possibility to set up the authorization via RFID card or without authorization. Additionally, Wallbox Adspace may have illuminated customer's logo in the middle of the housing.

Wallbox Duo Power

Provides the user with access to two 22 kW charging sockets each. Enelion is the only producer on the market offering so unique and compact solution.



Wallbox DUO



WALLBOX DUO



WALLBOX DUO POWER

TECHNICAL SPECIFICATION

Charging power	2x 1.4 kW – 7.4 kW	2x 1.4 kW – 22 kW
Socket	2 x type 2 socket	2 x type 2 socket
Communication module Bridge (OCPP 1.6)**	Offline / WiFi, Ethernet / LTE (GSM)	Offline / WiFi, Ethernet / LTE (GSM)
OLED Display / RFID / Buttons	Built-in	Built-in
Dynamic Load Balance (DLB)**	Enelion DLB	Enelion DLB
Energy meter	Built-in / Enelion MID*	Built-in / Enelion MID*
Residual current device**	RCM B / RCD A / RCD B	RCM B / RCD A / RCD B
Socket with lock	Built-in	Built-in
Impact protection	IK 10	IK 10
Ingress protection	IP 54	IP 54
Operating temperature	-25°C / +55°C	-25°C to +55°C
Height (mm)	250	250
Width (mm)	390	530
Depth (mm)	150	150

* certified energy measurement | ** optional equipment